

Water-based Black Impregnating Sealer & Restorer.

For Exterior Use.

For restoring the appearance of all types of faded pre-cast concrete and conglomerate stone surfaces. Helps prevent grout and jointing material from penetrating. Treated surfaces resist deep staining from organic matter and pollution making cleaning and removal of any stains much easier.

Directions for use

Preparation new surfaces: Ensure surface to be treated is as clean and as dry as possible. If necessary, first wash surfaces down with warm water. Scrub well using a white pad. Rinse well and leave overnight to dry.

Preparation older surfaces: Remove any blackspot, lichen, algae, mildew and stains from detritus using a good quality non acidic blackspot and algae remover. Rinse and leave to dry.

Wear gloves and ensure that any surfaces not to be treated are covered and protected.

IMPORTANT: This product is a permanent staining solution that will darken the surface and any pointing of grouting making it very difficult to remove once applied. Test on an inconspicuous area before general application and do not walk on treated surfaces until the solution has completely dried.

Shake bottle well before use: Apply a small amount to the surface and spread out evenly using a soft cloth or sealant applicator.

High porosity surfaces: apply with foam roller or paint brush. Allow to absorb and dry. Apply further coats (max 3) at 2 hourly intervals until desired depth of colour has been achieved. Leave to dry naturally.

Low porosity surfaces: once dry and to ensure even application it may be necessary to work any excess sealer using a soft cloth after 30 minutes.



COPING WITH THE DARKNESS

EXTERIOR USE

Restores and protects the appearance of dark grey and black cast stone

Allow newly treated surfaces to cure for 24 hours. Rub the surface with a white cloth or towel to make sure that it is completely colourfast.

Always experiment on a trial area first to establish optimum results.

Coverage (M ² per coat -- approx)	1 LTR
Lower porosity surfaces	30m ²
Higher porosity surfaces	15m ²

Storage information: Store in a cool, dry, frost-free environment. Shelf Life – Up to 2 years for un-opened containers.

Other: Empty containers are recyclable. Active ingredients are water soluble and inert once cured so therefore not harmful to the environment and ecologically sound. Do not apply when surface temperatures are under 5°C or over 25°C. Clean application tools and brushes with water after use.

HEALTH, SAFETY & ENVIRONMENTAL

Contains: 1,2-benzisothiazol-3(2H)-one;
1,2-benzisothiazolin-3-one(2634-33-5).
Keep out of reach of children.

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

1L^e

Eurodec Promenade Tiles LTD

The Highlands, Norton Ferris, Warminster, Wiltshire. BA12 7HT

T +44(0)1985 844669

E admin@promenadetiles.co.uk

www.promenadetiles.com